







Model	320W	400W	500W	600W	720W
Image					   
PRICE	<b>\$155.43</b>	<b>\$175.29</b>	<b>\$285.96</b>	<b>\$292.01</b>	<b>\$296.32</b>
Power consumption	320W	400W	500W	600W	720W
Lumen/watt	125 lm/W, 145lm/w, 165lm/watt				
Lumen	125 lm/W, 145lm/w, 165lm/watt				
Beam angle	30°	30°	30°, 60°, 90°	30°, 60°, 90°	30°, 60°, 90°
CCT	3000K-8000K , R/G/B/RGB/RGBW				
CRI	≥Ra70,80, 90				
LED	3030/5050/3535				
Working condition	-20°C ~ +50°C, 10%~90%RH				
Storage temp	-20°C ~ +50°C				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
In.V	AC 90V-305V / 347V / 480V				
Dimension/mm	446x400x321	446x400x321	537x480x373	537x480x373	537x480x373
Package/mm	465X475X445	465X475X445	588X588X445	588X588X445	588X588X445
Unit/carton	1PCS/carton				
Net weight /PCS	10kg	14.5kg	17kg	18.5kg	19.5kg
Gross weight /carton	12.5kg	16.5kg	19.5kg	21.5kg	23.0kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Installation	U bracket, etc				
Dimension					

SIDE A					
SIDE B					
SIDE C					

Model	400W	600W	1200W	1500W	1800W
Image					
PRICE	<b>\$163.89</b>	<b>\$216.48</b>	<b>\$446.78</b>	<b>\$665.85</b>	<b>\$672.76</b>
Power consumption	400W	600W	1200W	1500W	1800W
Lumen/watt	125 lm/W, 145lm/w, 165lm/watt				
Lumen	125 lm/W, 145lm/w, 165lm/watt				
Beam angle	7° /15° /30° /60° /90° /120° /T2M/T3M/T4M				
CCT	3000K-8000K , R/G/B/RGB/RGBW				
CRI	≥Ra70,80, 90				
LED	3030/5050/3535				
Working condition	-20℃~+50℃, 10%~90%RH				
Storage temp	-20℃~+50℃				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
In.V	AC 90V-305V / 347V / 480V				
Dimension/mm	531x377x129	637x462x129	678x869x129	678x1267x129	678x1267x129
Package/mm	558*432*172	672X534X188	932x718x198	1330x718x198	1330x718x198
Unit/carton	1PCS/carton				
Net weight /PCS	10/kg	14.5kg	32kg	46.5kg	46.5kg
Gross weight /carton	12.5kg	16.5kg	33kg	49.5kg	50.0kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Installation	U bracket, etc				
Dimension					
SIDE A					
SIDE B					
SIDE C					

Model	400W	650W	850W	1000W	1200W
Image					
PRICE	\$210.65	\$273.67	\$453.24	\$480.86	\$503.31
P.F	≥91%				
Electric efficiency	≥0.95				
LED Type	SMD 5050 / SMD3030				
Power consumption	400W	650W	850W	1000W	1200W
Lumen/watt	125 lm/W, 145lm/w, 165lm/watt				
CONTROL	DMX512, DALI, PLC, ZIGBEE, LORA, 0/1-10V DIMMING				
Beam angle	10°,25°,45°,60°				
CCT	3000K-8000K , R/G/B/RGB/RGBW				
CRI	≥Ra70,80,90				
LED	3030/5050				
Working condition	-20°C ~ +50°C, 10%~90%RH				
Storage temp	-20°C ~ +50°C				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
Dimension/mm	326*428*130	460*460*168	620*620*168	620*620*168	620*620*168
Package	365*465*165	525*525*250	685*685*250	685*685*250	685*685*250
Unit/carton	1PCS/carton				
Net weight /PCS	13.0kg	16.5kg	26.5KG	27.8KG	28.2KG
Gross weight/CTN	14.5kg	20kg	28.5kg	29.5kg	31.5kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Dimension	326*428*130	460*460*168	620*620*168	620*620*168	620*620*168
Installation A					
Installation B					
Installation C					
Installation	Round Bracket, Round Pole, U bracket, etc				




Round Bracket  
Black  
Die-cast Aluminum

























U Type Bracket  
Black  
Steel






Round Pole(Ø60mm)  
Black  
Die-cast Aluminum

Model	300W	600W	850W	1000W	1200W
Image					
PRICE	<b>\$152.41</b>	<b>\$280.29</b>	<b>\$468.61</b>	<b>\$496.64</b>	<b>\$521.17</b>
Power consumption	300W	600W	850W	1000W	1200W
Lumen	125 lm/W, 145lm/w, 165lm/watt				
Beam angle	60°, 90°, 120°	15°, 30°, 60°	15°, 30°, 60°	15°, 30°	15°, 30°
CCT	3000K-8000K , R/G/B/RGB/RGBW				
CRI	≥Ra70,80, 90				
LED	3030/5050/3535				
Working condition	-20°C ~ +50°C, 10%~90%RH				
Storage temp	-20°C ~ +50°C				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
In.V	AC 90V-305V / 347V / 480V				
Dimension/mm	463*440*220	652*565*350	652*565*350	730*640*390	1166*603*573
Package/mm	425*425*220	685*615*245	685*615*245	760*680*29	760*680*29
Unit/carton	1PCS/carton				
Net weight /PCS	9.5kg	18.5kg	18.5kg	26.5kg	26.5kg
Gross weight /carton	10.5kg	20.5kg	20.5kg	28.5kg	29.5kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Installation	U bracket, etc				
<b>Dimension</b>					
<b>SIDE A</b>					
<b>SIDE B</b>					
<b>SIDE C</b>					



Model	500W	1000W	1500W	1800W	2000W
Image					  
PRICE	<b>\$215.37</b>	<b>\$455.26</b>	<b>\$682.90</b>	<b>\$899.14</b>	<b>\$904.40</b>
Power consumption	500W	1000W	1500W	1800W	2000W
Lumen	125 lm/W, 145lm/w, 165lm/watt				
Beam angle	15° 30° 45° 60°				
CCT	3000K-8000K , R/G/B/RGB/RGBW				
CRI	≥Ra70,80, 90				
LED	3030/5050/3535				
Working condition	-20℃~+50℃, 10%~90%RH				
Storage temp	-20℃~+50℃				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
In.V	AC 90V-305V / 347V / 480V				
Dimension/mm	563*313*413	665*603*574	665*885*811	1166*603*573	1166*603*573
Package/mm	595*390*260	720*720*260	1060*720*260	1185*720*260	1185*720*260
Unit/carton	1PCS/carton				
Net weight /PCS	12kg	27kg	41kg	54.5kg	54.5kg
Gross weight /carton	14.5kg	30.5kg	43.5kg	58.5kg	59.5kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Installation	U bracket, etc				
<b>Dimension</b>					
<b>SIDE A</b>					
<b>SIDE B</b>					
<b>SIDE C</b>					

Model	150W	200W	240W	300W	400W	
Image					  	
PRICE	<b>\$106.75</b>	<b>\$109.89</b>	<b>\$111.72</b>	<b>\$207.48</b>	<b>\$217.41</b>	
Power consumption	150W	200W	240W	300W	400W	
Lumen	125 lm/W, 145lm/w, 165lm/watt					
Beam angle	20°、40°、60°、90°					
CCT	3000K-8000K , R/G/B/RGBW					
CRI	≥Ra70,80, 90					
LED	3030/5050/3535/7070					
Working condition	-40℃~+50℃, 10%~90%RH					
Storage temp	-40℃~+50℃					
Lifespan	≥50000 Hours ( 70000hours available )					
Structure	6063 Aluminium					
In.V	AC 90V-305V / 347V / 480V					
Dimension/mm	351*472*312	351*472*312	351*472*312	351*768*345	<b>351*768*345</b>	
Package/mm	380*210*150	380*210*150	380*210*150	380*235*255	380*235*255	
Unit/carton	1PCS/carton					
Net weight /PCS	4.95kg	5.25kg	5.35kg	10.98kg	12.85kg	
Gross weight/PCS	5.35kg	5.65kg	5.85kg	12.98kg	14.85kg	
Surge protection	10KV ( 20KV available )					
IP rating	IP65 ( IP67 available )					
Installation	U bracket, etc					
Installation						
	A	B	C	D		
						
						

Model	100W	150W	200W	240W	300W
Image					
	  				
PRICE	<b>\$42.07</b>	<b>\$53.32</b>	<b>\$64.21</b>	<b>\$77.80</b>	<b>\$90.20</b>
Power consumption	100W	150W	200W	240W	300W
P.F	≥91%				
Lumen	125 lm/W, 145lm/w, 165lm/watt				
Beam angle	Type III, Type IV				
CCT	3000K-8000K , R/G/B/RGBW				
CRI	≥Ra70,80, 90				
LED	3030/5050/3535				
Working condition	-20℃ ~ +50℃, 10%~90%RH				
Storage temp	-20℃ ~ +50℃				
Lifespan	≥50000 Hours ( 70000hours available )				
Structure	6063 Aluminium				
In.V	100-277V & 347-480VAC 50/60Hz				
Package/mm	550*290*130	620*320*130	640*370*135	640*370*135	730*390*145
Unit/carton	1PCS/carton				
Net weight /PCS	2.85kg	2.95kg	3.45kg	3.65kg	4.55kg
Gross weight /carton	3.05kg	3.25kg	3.85kg	4kg	4.65kg
Surge protection	10KV ( 20KV available )				
IP rating	IP65 ( IP67 available )				
Installation	slip filter, etc				
Dimension					
SIDE A					
SIDE B					
SIDE C					